

DATA SHEET 29720.125.43100

BG-72

A crystal clear film, for Colour Laser Printers using high fusing temperature toners. Ideally suited for overhead projection transparencies or see through overlays. The film uses the same universal coating on both sides, eliminating any confusion when inserting sheets into the feed tray.

Printing Systems



Formats

Art.Number	Format	Nominal thickness (mm)	Packing quantity
29720.125.44100	A4	0.125	50
29720.125.44000	A4	0.125	100
29720.125.43100	A3	0.125	50
29720.175.44100	A4	0.175	50

Technical data

Characteristic



- True colour
- Also suitable for machines with high fixing temperature
- Excellent runnability
- Good flatness
- Excellent toner bonding
- Heat resistant
- Highly universal

Finish

- Clear transparent

Specifications

Coating Printsideside	Laser & Copier colour
Width (inch)	11.69
Width (mm)	297
Printsideside	Printable both sides
Format	A3
Length (inch)	16.54
Length (mm)	420
Nominal thickness (mil)	5
Nominal thickness (mm)	0.125
Base Material	Polyester film
Packing quantity	50

Compatibility

- For use on most Mono & Colour Laser Printers.

Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Avoid moisture and fingerprints.

Storage

- Once packaging is opened, store at a room temperature of 15 - 25°C and at a humidity of 30 - 60 %
- Store in a cool and dry place
- Shelf life 1 year after delivery (under above storage conditions)

Safety instructions

- Only suitable for the use specified in this data sheet.
- The printing film may only come into direct contact with food or drinking water if there is a corresponding valid certificate for the product.
- Keep away from children. Not suitable for toy use.
- Keep away from heat sources as the material can be flammable.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.